



MODEL: #4272-DPW
ACRYLIC BATH ONLY: #4272-DPT






The acrylic whirlpool bath shall be model #4272-DTW (4272-DTT) as manufactured by Laurel Mountain Whirlpools, Inc. It shall be constructed of .125 thick cast acrylic sheet, backed by layers of polyester resin and fiberglass roving. It will be mounted on a FRP pre-leveled pump-base and two PVC/fiberglass legs. All components will be UL listed and approved. The pump motor will be 21/4 horsepower (1 phase, 115V, 60HZ, 3450 RPM, pre-mounted) and the plumbing system will be rigid PVC. The unit will contain 6 multi-directional jets, one air control and a safety suction fitting. Access to pump and plumbing system must be provided by installer in accordance with established plumbing and electrical codes.

ELECTRICAL SPECIFICATIONS - 115V, 20 AMP, GFCI Protected Circuit.

SPECIFICATIONS W	HIRLPOOL	Tub
41 ½ x 71 ¾ x 23 Lip 2"		
Water Capacity - Operating Level	-	27.0 . 1
- To Overflow	87.0 gal. 147.0 lbs.	87.0 gal. 112.0 lbs.
Approx. Shipping Weight	212.0 lbs.	177.0 lbs.

*All dimensions are \pm */- 3/8" and subject to change without notice. Always pre-measure tub/whirlpool prior to framing alcove or creating deck installation cut out.



PUMP MOTOR: Standard $1^{1/4}$ HP, SIngle Phase, 115V, 60HZ, 3425 RPM, Pre-installed (factory)

ELECTRICAL REQUIREMENTS: 115V, 20 AMP, GFCI Protected Circuit.

CORPORATE SALES AND MANUFACTURING HEADQUARTERS



Laurel Mountain Whirlpools, Inc.

P.O. Box 190 1210 Airbrake Ave. Turtle Creek, PA 15145-0190 TELEPHONE
412-829-2540
800-930-0050
E-MAIL: sales@laurel
mountainwhirlpools.com

FAX 412-829-1670 800-930-0051

www.laurelmountainwhirlpools.com